

SECTION 1 Identification

Product Name: CONOSTAN[®] D-Series D-12 Standard
Chemical Family Petroleum hydrocarbon
Intended Use Instrument Calibration
Catalogue Number: 150-300-002

Recommended Use: Laboratory Chemical
Instrument Calibration. This product is intended for laboratory testing. This product shall be used by trained personnel only.

Restriction on use:
Do not use this product outside of a laboratory. This product should not be used by untrained personnel.

Manufacturer/ Supplier:**Canada/ International**

21 800 Clark-Graham
Baie d'Urfé, (Montreal)
Québec, H9X 4B6
Canada

Phone: +1 (800) 361-6820
Fax: +1 (800) 253-5549

USA

3rd Party Distribution Center
348 Route 11, Champlain,
N.Y. 12919-4816
USA

Phone: +1 (800) 361-6820
Fax: +1 (800) 253-5549

France

12 Ave du Québec
Bât Iberis, SILIC 642
91965 Courtaboeuf,
France

Phone: +33 (0) 1 69 18 71 17
Fax: +33 (0) 1 60 92 05 67

Germany

Alte Marktoberdorfer
Straße 14, 87616
Marktoberdorf
Germany

Phone: +49 (0) 8342-89560-61
Fax: +49 (0) 8342-89560-69

CORPORATE : Phone: +1 (514) 457-0701 | Fax: +1 (514) 457-4499 | www.scpscience.com | sales@scpscience.com

For Spills, Leaks, Fires or Accidents Call CHEMTREC: North America: (800) 424-9300
Others: (703) 527-3887 (collect)
California Poison Control System: (800) 356-3129

In the event of medical emergency, call your local poison centre or equivalent.

SECTION 2 Hazards Identification**Emergency Overview****GHS**

Harmonized Classification – Annex VI of Regulation (EC) No 1272/2008 (CLP Regulation)

Classification: Carcinogen - Category 1 B

Pictograms:



Signal Word: Danger

Hazard Statements

H350: May cause cancer.

Precautionary Statements

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P281: Use personal protective equipment as required.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P405: Store locked up.

P501: Dispose of contents/container according to federal, regional and local government requirements.

Other Hazards: No information available

SECTION 3 Composition and Information on Ingredients

CAS No.	Chemical Name	Weight	Classification ((EC) No 1272/2008)
Mixture	Lubricant Base Oil	98-100%	H350 - Carc. 1B
None	Oil Mist, If generated	---	Not classified

The following materials are present at less than 0.1%:
Blended Alkyl aryl Sulfonate or as indicated, including

Silver Compound	- % as Ag
Aluminum Compound	- % as Al
Chromium Compound	- % as Cr
Copper Compound	- % as Cu
Iron Compound	- % as Fe
Magnesium Compound	- % as Mg
Sodium Compound	- % as Na
Nickel Compound	- % as Ni
Lead Compound	- % as Pb
Silicon Compound	- % as Si
Tin Compound	- % as Sn
Titanium Compound	- % as Ti

A typical concentration of the above metal compound is 100 ppm.
Refer to container for the exact concentration.

1% = 10,000 PPM.

SECTION 4 First Aid Measures

In case of contact:

- Eye:** Move victim away from exposure and into fresh air. If irritation or redness develops, flush eyes with clean water and seek medical attention. For direct contact, hold eyelids apart and flush the affected eye(s) with clean water for at least 15 minutes. Seek medical attention.
- Skin:** Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops, seek medical attention.
- Ingestion:** Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical attention.
- Inhalation:** Immediately move victim away from exposure and into fresh air. If respiratory symptoms or other symptoms of exposure develop, seek immediate medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical

attention.

Most important Symptoms:

Not available.

Notes to Physician/Doctor:

Acute aspirations of large amounts of oil-laden material may produce serious aspiration pneumonia. Patients who aspirate these oils should be followed for development of long-term sequelae. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

SECTION 5 Fire-fighting Measures

Fire Hazard Summary:

For fires beyond the incipient stage, emergency responders in the immediate hazard areas should wear bunker gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when explicitly required by DOT, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (See Section 8).

Isolate immediate hazard area, keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from the immediate hazard area if it can be done with minimal risk.

Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

Extinguishing Media:

Dry chemical, carbon dioxide, foam or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

Extinguishing Media to be Avoided:

Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible.

Combustion and Thermal Decomposition Products:

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, or mechanical/electrical equipment). May create vapor/air explosion hazard if heated. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION

Health: 1 – Exposure would cause irritation with only minor residual injury.
Flammability: 0
Reactivity: 0
Special Hazard:

SECTION 6 Accidental Release Measures

Spill Precautions:

Notify persons downwind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it is safe to do so. Wear appropriate protective equipment including respiratory protection as conditions warrant (See Section 8).

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways. Dike far ahead of the spill for later recovery or disposal. Spilled material may be absorbed into an appropriate absorbent material.

Notify fire authorities and appropriate federal, state and local agencies. Immediate cleanup of any spill is recommended. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, notify the National Response Center (Phone No.: 800-424-8802).

Clean-up:

SMALL SPILLS: Not applicable.

LARGE SPILLS: Evacuate area. Contact fire and emergency services and supplier for advice.

SECTION 7 Handling and Storage**Handling:**

Handle in well ventilated area. Handle away from heat and sources of ignition. Use normal laboratory protective equipment, including gloves and safety glasses

Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames. Use good personnel hygiene practices.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum re-conditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Storage:

Keep container(s) tightly closed. Use and store this material in a cool, dry, well-ventilated area, away from heat and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (See Section 10). Protect container(s) against physical damage.

Additional Information:

The mixture is intended for use in a laboratory. The mixture as supplied is stable under normal laboratory conditions.

SECTION 8 Exposure Controls and Personal Protection**EXPOSURE GUIDELINES**

Oil mist if generated

ACGIH: 5 mg/m³ TWA (Inhalable fraction); 10 mg/m³ STEL

OSHA: 5 mg/m³ TWA (Related to oil mist)

NIOSH: 5 mg/m³ TWA

NOTE: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Preventive Measures: Effects of overexposure include irritation of the nose and throat. Repeated skin contact can cause irritation, reddening. Hazardous if swallowed.

Avoid inhaling vapors. Avoid contact with eyes and skin. Do not taste or swallow. Wash thoroughly after handling.

Eye / Face protection: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended. Depending on conditions of use, a face shield may be necessary.

Skin protection: The use of gloves impervious to the specific material handled is advised to prevent skin contact and possible irritation (see manufacturers literature for information on permeability). Examples of approved materials are nitrile, Viton.

Inhalation / Ventilation: A NIOSH certified air purifying respirator may be used.

Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a NIOSH approved self-contained breathing apparatus (SCBA) or equivalent operated in a pressure demand or other positive pressure mode if there is potential for an uncontrolled release, exposure levels are unknown, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2

Personal Hygiene:	requirements must be followed whenever workplace conditions warrant a respirator's use. Do not eat or drink in work areas. Wash hands thoroughly after handling this material. Maintain good housekeeping. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Appropriate Engineering Controls:	If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits (See exposure guidelines), additional engineering controls may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used (See appropriate electrical codes).
Other Protective Equipment:	Eye wash and quick-drench shower facilities should be available for flushing eyes and skin. Impervious clothing should be worn as needed. Thoroughly clean shoes and wash contaminated clothing before reuse. It is recommended that impervious clothing be worn when skin contact is possible.

Suggestions for the use of specific protective materials are based on readily available published data. Users should check with specific manufacturers to confirm the performance of their products.

SECTION 9 Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State	Liquid
Appearance	Amber
Odor	Hydrocarbon
Property Values	
pH VALUE	No data available
Melting Point/Range	No data available
Boiling Point/Range	c. 400-550°F / 204-288°C
Evaporation rate	Negligible
Flammability (solid, gas)	No data available
Vapor Pressure	<1
Vapor Density	6.2
Relative Density	No data available
Specific Gravity	c. 0.81 – 0.89
Water Solubility	Negligible
Partition coefficient: n-octanol/water	No data available
Auto ignition Temperature	No data available
Decomposition Temperature	No data available
Viscosity (@ 40 °C)	No data available

SECTION 10 Stability and Reactivity

Chemical stability:	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Incompatible Materials:	Avoid contact with strong oxidizing agents.
Conditions to avoid:	Avoid all possible sources of heat and ignition (See Sections 5 and 7).
Hazardous Decomposition Products:	Combustion can yield carbon dioxide, carbon monoxide and other oxides.
Hazardous Polymerization:	Will not occur.

SECTION 11 Toxicological Information

Potential Health Effects

Eye:	Contact may cause mild eye irritation including stinging, watering and redness.
Skin:	Mild to moderate skin irritant. Contact may cause redness, itching, burning and skin damage. Prolonged or repeated contact may cause drying and cracking of the skin, dermatitis (inflammation), burns and sever skin damage. Not acutely by skin absorption but prolonged or repeated skin contact may be harmful.
Ingestion:	May be harmful if ingested.
Inhalation:	May be harmful by inhalation.

Effects of Short-Term (Acute) Exposure

LD50/LC50:	LD50: 5 000 mg/Kg (Rat). LD50: 2 000 mg/Kg (Rabbit).
-------------------	---------------------------------------------------------

Effects of Long-Term (Chronic) Exposure

Respiratory or skin sensitization:	No information found.
Germ Cell Mutagenicity:	Testing of various nickel compounds has produced positive results in assays for gene mutation, chromosomal aberration and DNA damage in both bacterial and mammalian cells.
Reproductive Toxicity:	Administration of certain organic lead compounds during pregnancy has caused developmental toxicity (neurobehavioral effects) in laboratory animals.

Administration of nickel acetate during pregnancy has resulted in birth defects in sheep, hamsters and mice. Developmental defects affects primarily the eyes were noted in laboratory animals exposed to nickel carbonyl via inhalation during pregnancy. Administration of soluble inorganic salts of nickel during pregnancy resulted in limited evidence of developmental toxicity. Increased fetal death, decreased litter size and reduced fetal weights were noted, but only at concentrations that also compromised the health status of the mothers. There is inconclusive evidence for the developmental toxicity of insoluble inorganic salts (e.g., oxides and sulfides).

STOT- Single exposure	No definitive information available on target organs toxicity short term exposure.
STOT- Repeated exposure	Chronic overexposure to organic lead compounds is associated with toxicity of the hematopoietic, vascular, male reproductive, nervous systems and of the kidney. Hematological effects include anemia, decreased hemoglobin and increased urinary porphyrins. Vascular effects are manifested as high blood pressure. Neurotoxic effects may involve both sensory and motor neurons and may include encephalopathy and peripheral neuropathy. Kidney damage is characterized by nephropathy, interstitial fibrosis and tubular damage. Effects on the male reproductive system may include decreased sperm count, motility and testicular atrophy.

Chronic exposure to nickel and certain nickel compounds can cause rhinitis, sinusitis, allergies, cancer of the nasal sinus cavities and lungs. Nasal polyps, perforation of the nasal septum and chronic pulmonary irritation have also been reported. There is limited evidence from laboratory animal studies that nickel sulfate and nickel chloride can adversely affect the male reproductive system.

Aspiration Hazard:	No definitive information available.
Carcinogenicity:	Chronic oral ingestion of various inorganic lead compounds resulted in increased renal

tumors in laboratory animals. Lead and inorganic lead compounds have been identified as carcinogens by NTP, IARC and OSHA. Organic lead compounds have not been identified as a carcinogen by NTP, IARC or OSHA.

There is insufficient evidence in humans for the carcinogenicity of nickel sulfate and for nickel compounds (sulfides and oxides) encountered in nickel refining. There is sufficient evidence in animals for the carcinogenicity of metallic nickel, nickel monoxides, nickel hydroxides and crystalline nickel sulfides and limited evidence in animals for other nickel compounds (e.g., alloys, arsenides and nickel carbonyl). Occupational exposure has been associated with cancer of the lung and nasal cavity. Nickel and nickel compounds have been identified as carcinogens by NTP and IARC.

Prolonged and repeated skin exposure of mice to certain middle distillate streams has resulted in dermatitis, which has been associated with the promotion of skin tumors via a non-genotoxic mechanism.

No definitive information available for the other components on carcinogenicity, mutagenicity, target organs or developmental toxicity.

Signs and symptoms of exposure:

Overexposure: Effects of overexposure may include diarrhea, irritation of the digestive tract and irritation of the respiratory tract.

SECTION 12 Ecological Information

Eco-toxicity: no information about this preparation is available.

Mobility in soil: no information about this preparation is available.

Persistence and degradability: no information about this preparation is available.

Bioaccumulative potential: no information about this preparation is available.

SECTION 13 Disposal Considerations

Product disposal:

This product is known to be a hazardous waste. However, it should be fully characterized for toxicity prior to disposal (40 CFR 261). Along with properly characterizing all waste materials, consult state and local regulations regarding the proper disposal of this material.

Container contents should be completely used and containers should be emptied prior to discard. Container rinsate could be considered a RCRA hazardous waste and must be disposed of with care and in full compliance with federal, state and local regulations. Larger empty containers, such as drums, should be returned to the distributor or to a drum re-conditioner. To assure proper disposal of smaller empty containers, consult with state and local regulations and disposal authorities.

Contaminated packaging: Dispose of as unused product.

SECTION 14 Transport Information

IDMG (sea): Not Regulated As A Hazardous Material Or Dangerous Goods For Transportation By This Agency.

ADR/DOT (road): Not regulated

Material is unregulated unless in container of 3500 gal or more then provisions of 49 CFR Part 130 apply for land shipment.

ICAO/IATA (air): Not Regulated As A Hazardous Material Or Dangerous Goods For Transportation By This Agency.

SECTION 15 Regulatory Information

US Federal:

TSCA

This product and/or its components are listed on the TSCA Chemical Inventory.

US State:

Warning: This material contains the following chemicals which are known to the state of California to cause cancer, birth defects or other reproductive harm, and are subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

California Prop. 65

Component: Lead and Lead Compounds
Effect: Cancer

Component: Nickel and Certain Nickel Compounds
Effect: Cancer

This material has not been identified as a carcinogen by NTP, IARC or OSHA except for some individual components.

Canada

WHMIS Classifications:

D2B – Materials causing other toxic effects

EU

EU Symbol:

Carc.

Risk Phrase(s):

R45: May cause cancer.

SECTION 16 Other Information

Revised:

August 22, 2018

Date of previous revision (s):

July 19, 2017

Hazard Indications (H) Regulation (EC) No 1272/2008 quoted in Sections 3.

Carc. 1B

Carcinogenicity

H350

May cause cancer.

The statements contained herein are offered for informational purposes only and are based upon technical data. SCP SCIENCE believes them to be accurate but does not purport to be all-inclusive. The above-stated product is intended for use only by persons having the necessary technical skills and facilities for handling the product at their discretion and risk. Since conditions and manner of use are outside our control, we make no warranty of merchantability or any such warranty, express or implied with respect to information and we assume no liability resulting from the above product or its use. Users should make their own investigations to determine suitability of information and product for their particular purposes.

This safety data sheet has been prepared in conformance with GHS (Global Harmonised System) Guidance on the Preparation of Safety Data Sheets (SDS) Copyright © United nations, 2011.