



Safety Data Sheet

SECTION 1 Identification

Product Name: CONOSTAN® Sulfur (S) Standard

Matrix: Petroleum hydrocarbon
Intended Use: Instrument Calibration

Catalogue Number: 150-400-001

Recommended Use: Laboratory Chemical

Instrument Calibration. This product is intended for laboratory testing. This

product shall be used by trained personnel only.

Restriction on use: Do not use this product outside of a laboratory. This product should not be used

by untrained personnel.

Manufacturer/ Supplier:

Canada/ International France

21 800 Clark-Graham 12 Ave du Québec

Baie d'Urfé, (Montréal) Bât Iris,

Québec, H9X 4B6 91140 Villebon sur Yvette,

Canada France

Phone: +1 (800) 361-6820 Phone: +33 (0) 1 69 18 71 17 Fax: +1 (800) 253-5549 Fax: +33 (0) 1 60 92 05 67

CORPORATE: Phone: +1 (514) 457-0701 | Fax: +1 (514) 457-4499

www.scpscience.com | salesNA@analytichem.com

In the event of a transport emergency, call Chemtrec (24 h): 1-703-741-5970 (CHEMTREC)

California Poison Control System: (800) 356-3129

In the event of medical emergency, call your local poison center or equivalent.

SECTION 2 Hazards Identification

Emergency Overview

GHS

Harmonized Classification - Annex VI of Regulation (EC) No 1272/2008 (CLP Regulation)

Classification: Not Classified Symbols: Not Classified

Signal Word:Not ClassifiedHazard StatementsNot ClassifiedPrecautionary StatementsNot Classified

Other Hazards: No information found.

SECTION 3 Composition and Information on Ingredients

CAS No. Chemical Name % Weight Classification ((EC) No 1272/2008)

8042-47-5 White Mineral Oil (75 cSt) 100% Not classified

None Oil Mist, If generated --- None

The following materials are present at less than 0.1% Blended Alkyl aryl Sulfonate or as indicated, including

Di-n-butyl sulfide - % as S

A typical concentration of above metallic compounds is 0 - 10 ppm.

Refer to container for the exact concentration.

1% = 10,000 PPM.

SECTION 4	First Aid Measures

In case of contact:

Eye: If irritation or redness develops, move victim away from exposure and into fresh

air. Flush eyes with clean water. If symptoms persist, seek medical attention.

Skin: Remove contaminated shoes and clothing and flush affected area(s) with large

amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness

develops, seek medical attention.

Ingestion: Do not induce vomiting or give anything by mouth because this material can

enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical

attention.

Inhalation: If respiratory symptoms develop, move victim away from source of exposure and

into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek

immediate medical attention.

Most important Symptoms: May be harmful or fatal if swallowed.

Notes to Physician/Doctor:

Acute aspirations of large amounts of oil-laden material may produce serious

aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treat symptomatically.

SECTION 5 Fire-fighting Measures

Fire Hazard Summary:

For fires beyond the incipient stage, emergency responders in the immediate hazard areas should wear bunker gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when explicitly required by DOT, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (See Section 8).

Isolate immediate hazard area, keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from the immediate hazard area if it can be done with minimal risk.

Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can

be done with minimal risk. Avoid spreading burning liquid with water

used for cooling purposes.

Extinguishing Media: Dry chemical, carbon dioxide, foam or water spray is recommended.

Water or foam may cause frothing of materials heated above 212°F. Carbon dioxide can displace oxygen. Use caution when applying carbon

dioxide in confined spaces.

Extinguishing Media to b

Avoided:

be No information found.

Combustion and Thermal Decomposition Products:

This material may burn, but it will not ignite readily. If container is not

properly cooled, it can rupture in the heat of a fire.

Special protective equipment and precautions for fire-fighters:

Firefighters should wear self-contained respirator and full protective $% \left(1\right) =\left(1\right) \left(1\right) \left($

gear.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION

Health: 0 - Poses no health hazard, no precautions necessary

Flammability: 1 - Must be heated before ignition can occur.

Reactivity: 0- Normally stable, even under fire exposure conditions, and is not

reactive with water

Special Hazard:

SECTION 6 Accidental Release Measures

Spill Precautions:

Keep all sources of ignition away from spill/release. Stay upwind and away from spill/release. Notify persons downwind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant (See Section 8).

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways. Dike far ahead of the spill for later recovery or disposal. Spilled material may be absorbed into an appropriate absorbent material.

Notify fire authorities and appropriate federal, state and local agencies. Immediate cleanup of any spill is recommended. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, notify the National Response Center (Phone No.: 800-424-8802).

Personal precautions: Wear appropriate protective equipment including respiratory protection as conditions warrant (See Section 8).

Protective equipment and emergency procedures: Ensure adequate ventilation. Evacuate personnel to safe areas.

SMALL SPILLS: Not applicable.

LARGE SPILLS: Evacuate area. Contact fire and emergency services and supplier

for advice.

SECTION 7 Handling and Storage

Handling:

Clean-up:

Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames. Use good personnel

hygiene practices.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum re-conditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Storage: Keep container(s) tightly closed. Use and store this material in a cool, dry, well-

ventilated area, away from heat and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (See Section

10). Protect container(s) against physical damage.

Additional Information: The mixture is intended for use in a laboratory. The mixture as supplied is stable

under normal laboratory conditions.

SECTION 8 Exposure Controls and Personal Protection

Exposure guidelines

ACGIH: Oil Mist, If generated- 5 mg/m3 (TWA), 10 mg/m3 (STEL).

NOTE: State, local or other agencies or advisory groups may have established

more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Preventive Measures: Combustible liquid and vapor. Keep away from heat sparks, flames,

static electricity or other sources of ignition.

Eye / Face protection: Approved eye protection to safeguard against potential eye contact,

irritation or injury is recommended. Depending on conditions of use, a

face shield may be necessary.

Skin protection: The use of gloves impervious to the specific material handled is advised

to prevent skin contact and possible irritation (see manufacturers literature for information on permeability). Examples of approved

materials are nitrile, neoprene.

Inhalation / Ventilation: A NIOSH certified air purifying respirator with a Type 95 (R or P)

particulate filter may be used under conditions where airborne concentrations are expected to exceed exposures limits (See exposure

guidelines).

Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a NIOSH approved self-contained breathing apparatus (SCBA) or equivalent operated in a pressure demand or other positive pressure mode if there is potential for an uncontrolled release, exposure levels are unknown, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Personal Hygiene: Do not eat or drink in work areas. Wash hands thoroughly after handling

this material. Maintain good housekeeping. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks

and at the end of workday.

Appropriate Engineering

Controls:

If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits (See exposure guidelines), additional engineering controls may be required. Where explosive mixtures may be present, electrical systems safe for such

locations must be used (See appropriate electrical codes).

Other Protective Equipment: Eye wash and quick-drench shower facilities should be available for

flushing eyes and skin. Impervious clothing should be worn as needed. Thoroughly clean shoes and wash contaminated clothing before reuse. It is recommended that impervious clothing be worn when skin contact

is possible.

Suggestions for the use of specific protective materials are based on readily available published data. Users should check with specific manufacturers to confirm the performance of their products.

SECTION 9 Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Liquid

Appearance Clear / Colorless
Odor Hydrocarbon

Property Values

pH VALUEMelting Point/RangeNo data available

Boiling Point/Range c. 218 to 800°C (424.4 to 1472°F)

Evaporation rate

Flammability (solid, gas)

Vapor Pressure (mmHg)

Vapor Density

Bulk Density

No data available
No data available
No data available
c. 6.25 lbs/gal

Specific Gravity c. 0.6 - 0.9 @ 60°F (15.6°C)

Water Solubility
Partition coefficient: n-

octanol/water

No data available

Not Soluble

Auto ignition Temperature

Decomposition Temperature

Viscosity

No data available

C. 65 - 72 cSt

Flash Point

No data available

SECTION 10 Stability and Reactivity

Reactivity: No information found.

Chemical stability: Stable at room temperature and conditions of use.

Incompatible Materials: Avoid contact with strong oxidizing agents.

Conditions to avoid: High temperatures. Avoid all possible sources of ignition (See Sections 5

and 7).

Hazardous Decomposition

Products:

Combustion can yield carbon, carbon oxides.

Hazardous Polymerization: Will not occur.

SECTION 11 Toxicological Information

Potential Health Effects

Eye: Contact may cause mild eye irritation.

Skin: Contact may cause irritation.

Ingestion: No information found.

Inhalation: Overheating of product may produce vapors which can cause respiratory

irritation, dizziness and nausea.

Effects of Short-Term (Acute) Exposure

LD50/LC50: No information found.

Effects of Long-Term (Chronic) Exposure

Respiratory or skin No information found.

sensitization:

Germ Cell Mutagenicity: No component of this product at levels greater than 0.1% is classified as

a mutagen.

Reproductive Toxicity: No component of this product at levels greater than 0.1% is classified for

reproductive toxicity.

STOT- Single exposure No definitive information found for target organs toxicity.

STOT- Repeated exposure No definitive information found for target organs toxicity, repeated

exposure.

Aspiration Hazard: No information found.

Carcinogenicity: Not listed as a carcinogen by NTP, or CA Prop 65.

No evidence of cancer has been demonstrated in several well conducted

animal studies.

No evidence of cancer has been demonstrated for this product.

Signs and symptoms of exposure:

Eye: Contact may cause mild eye irritation.

Skin: Contact may cause irritation. Inhalation: No information found.

Ingestion: Overheating of product may produce vapors which can cause respiratory

irritation, dizziness and nausea.

SECTION 12 Ecological Information

Eco- toxicity:

Mobility in soil:

Persistance and degradability:

Bioaccumulative potential:

no information found for this preparation.
no information found for this preparation.
no information found for this preparation.

SECTION 13 Disposal Considerations

Product disposal: This material, if discarde

This material, if discarded as produced, is not a RCRA "listed" hazardous waste. However, it should be fully characterized for toxicity prior to disposal (40 CFR 261). Use which results in chemical or physical change or contamination may subject it to regulation as a hazardous waste. Along with properly characterizing all waste materials, consult state and local regulations regarding the proper disposal of this material.

Container contents should be completely used and containers should be emptied prior to discard. Container rinsate could be considered a RCRA hazardous waste and must be disposed of with care and in full compliance with federal, state and local regulations. Larger empty containers, such as drums, should be returned to the distributor or to a drum re-conditioner. To assure proper disposal of smaller empty containers, consult with state and local regulations and disposal

authorities.

Contaminated packaging: Dispose of as unused product.

SECTION 14 Transport Information

IMDG (sea): Not Regulated As A Hazardous Material Or Dangerous Goods For

Transportation By This Agency.

UN-Number:

Class:

Packing group:

Proper shipping name: Marine pollutant:

ADR/DOT (road): Not regulated

Material is unregulated unless in container of 3500 gal or more then

provisions of 49 CFR Part 130 apply for land shipment.

UN-Number:

Class:

Packing group:

Proper shipping name: Marine pollutant:

ICAO/IATA (air): Not Regulated As A Hazardous Material Or Dangerous Goods For

Transportation By This Agency.

UN-Number:

Class:

Packing group:

Proper shipping name: Marine pollutant:

SECTION 15 Regulatory Information

US Federal:

TSCA: All components are listed on the TSCA Inventory.

US State:

California Prop. 65: This material do not contain any chemical which are known to the state

of California to cause cancer, birth defects or other reproductive harm, and are subject to the requirements of California Proposition 65 (CA

Health & Safety Code Section 25249.5).

Canada

WHMIS Classifications: Not Applicable

EU

Classifications: Not Applicable Risk Phrase(s): Not Applicable

SECTION 16 Other Information

Revised: March 18, 2024

Date of previous revision(s): Not available

Hazard Indications (H) Regulation (EC) No 1272/2008 quoted in Sections 3.

Not classified

The statements contained herein are offered for informational purposes only and are based upon technical data. SCP SCIENCE believes them to be accurate but does not purport to be all-inclusive. The above-stated

This safety data sh	neet has been pr	epared in conf	ormance with	GHS (Global Ha		
on the Preparation	of Safety Data S	heets (SDS) Co	pyright © Unite	ed nations, 201	1.	